

|          |                       |
|----------|-----------------------|
| DOCUMENT | BXPFAT600400210-P01   |
| VERSION  | 1.0                   |
| FORM     | TECHNICAL INFORMATION |



## WALL MOUNTING CABINET SERIES PERLE

ORDER NO.: BXPFAT600400210-P01

EAN: 6418074080035



Sample Picture

### DESCRIPTION

|                           |                                                                                                                         |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>PRODUCTTYPE:</b>       | WALL MOUNTING CABINET                                                                                                   |
| <b>OUTER DIMENSIONS:</b>  | 600x400x210 mm                                                                                                          |
| <b>INNER DIMENSIONS:</b>  | 561x361,5x204 mm (MINUS MOUNTING AREA)                                                                                  |
| <b>CLOSURE:</b>           | TRANSPARENT DOOR WITH HINGE ON THE LONG SIDE AND 2-POINT CLOSURE                                                        |
| <b>COLOUR:</b>            | RAL7035 LIGHT GREY                                                                                                      |
| <b>WEIGHT:</b>            | 840g                                                                                                                    |
| <b>MATERIALS:</b>         | POLYCARBONATE                                                                                                           |
| <b>EAN:</b>               | 6418074080035                                                                                                           |
| <b>SCOPE OF DELIVERY:</b> | CONTROL CABINET BASE, DOOR WITH PUR SEAL, MOUNTING PLATE (STEEL, GALVANIZED), MOUNTING SCREWS, 3MM DOUBLE-BIT SASH LOCK |

### TECHNICAL DATA

|                                   |                                                   |
|-----------------------------------|---------------------------------------------------|
| <b>PROTECTION:</b>                | IP 66 AS PER DIN EN 60529/DIN 40050               |
| <b>IMPACT RESISTANCE:</b>         | IK10 +35°C /IK08 -25°C as per IEC 62262, EN 50102 |
| <b>AMBIENT TEMPERATURE RANGE:</b> | -40°C ... +80°C as per DIN EN 60670               |

### ACCESSORIES

|                               |           |
|-------------------------------|-----------|
| <b>MOUNTING PLATE:</b>        | INCLUDED  |
| <b>WALL MOUNTING BRACKET:</b> | AVAILABLE |
| <b>CABEL GLAND:</b>           | AVAILABLE |
| <b>CORNER PROFILES:</b>       | AVAILABLE |
| <b>RAIN PROTECTION:</b>       | AVAILABLE |

|          |                       |
|----------|-----------------------|
| DOCUMENT | BXPFAT600400210-P01   |
| VERSION  | 1.0                   |
| FORM     | TECHNICAL INFORMATION |

## TECHNICAL DRAWING

