

DOCUMENT	BXPIPOLG360270171-P01
VERSION	1.0
FORM	TECHNICAL INFORMATION



IP66 POLYESTER ENCLOSURE WITH DOUBLE INSULATION

ORDER NO.:
BXPIPOLG360270171-P01



Sample

DESCRIPTION

PRODUCT TYPE:	IP66 POLYESTER ENCLOSURE WITH DOUBLE INSULATION
OUTER DIMENSIONS:	360X270X171MM (HxWxL)
USABLE SPACE INSIDE:	340X250x154MM (HxWxL)
INSTALLATION:	SURFACE MOUNTED
DOOR TYPE:	OPAQUE DOOR
LOCKING:	SCREWS FOR FASTENING WITH SCREWDRIVER
COATING:	DOUBLE INSULATION: PROTECTION CLASS II
COLOR:	RAL 7035
MOUNTING PLATE:	WITHOUT MOUNTING PLATE (AVAILABLE SEPARATELY)
WEIGHT (KG):	2
MATERIAL:	GLASS FIBER REINFORCED POLYESTER
FOAMED GASKET:	FOAMED POLYURETHANE GASKET
DOOR MATERIAL:	POLYCARBONAT

TECHNICAL DETAILS

PROTECTION CLASS:	IP 66
IMPACT PROTECTION:	IK 09
AMBIENT TEMPERATURE RANGE:	-30°C / +60°C
MAXIMUM OPERATING VOLTAGE:	1000V AC / 1500V DC

DOCUMENT	BXPIPOLG360270171-P01
VERSION	1.0
FORM	TECHNICAL INFORMATION

CERTIFICATIONS AND STANDARDS:

DIRECTIVE:

2014/35/EU

NORMS:

IEC 62208, IEC 61439-1

TECHNICAL DRAWING

